## CODE NUMBER

3362157IN

## DESCRIPTION

4" Trim Plate, Plug Adapter Power Supply, Back-Check Tee, Polished Chrome Finish, 0.5 gpm, Multi-Laminar Spray, Infrared Sensor, Sloan® Hardwired-Powered Deck-Mounted Low Body.

## DETAILS

- Flow Rate: 0.5 gpm (1.9 Lpm) (0.5GPM)
- Spray Type: Multi-Laminar (MLM)
- Sensor Type: Infrared
- Mounting Type: Single Hole
- Trim Plate: 4" (102mm) (4)
- Power Supply: Plug Adapter (PLG)
- Temperature Mixer: Back-Check Tee (TEE)
- Finish: Polished Chrome (CP)
- Factory Default Timeout: 30 seconds
- Factory Default Gallons per Cycle: 0.25

## FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Brass Pedestal Hand Washing Faucet with the following features:

- Adjustable Infrared Sensor Range
- 36" (914 mm) Long Sensor Cable
- 24" (610 mm) Long Flex Hose
- Filtered Solenoid Valve with serviceable Strainer Filter
- Includes Four (4) AA-size Batteries
- Includes appropriate Mounting Hardware

## ELECTRICAL SPECIFICATIONS

- Battery Life: 2 years 8,000 cycles/month
- Sensor Range: 4"–7" (102–178mm)
- Timeout Adjustment Settings: 30s

## VIDEOS

- ▶ SF-2100/2150/SF-2200/2250/SF-2300/2350/SF-2400/2450 Parts Breakdown
- ▶ SF-2100/2150/SF-2200/2250/SF-2300/2350/SF-2400/2450 Module Replacement
- ▶ SF-2100/2150/SF-2200/2250/SF-2300/2350/SF-2400/2450 Battery Replacement- Sensor Range Adjustment

## DOWNLOADS

- SF Series Installation Instructions
- SF Series (FR) Installation Instructions
- SF Series (SP) Installation Instructions
- SFP 35-A Installation Instructions
- SF 2100/2150 Faucet Extension Installation Instructions
- Trim Plate Guide
- Sloan 2100/2150 Repair and Maintenance Guide
- Faucet Spray Heads Repair and Maintenance Guide





## COMPLIANCES & CERTIFICATIONS



(ADA Compliant, ASME A112.18.1 Compliant, cUPC Certified, UPC Certified, UPC Low Lead Compliant, cUPC Low Lead Compliant, IAPMO, WaterSense Listed, NSF-61, Proposition 65, WELL Building Standard)

## NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the SF-2100 product? View the general spec sheet with all options.

Find a matching soap dispenser for this faucet.
Find a compatible sink for this faucet.

## WARRANTY

View Warranty Information

● Additional Downloads

**ROUGH-IN**

2-1/8"
(54 mm)

SPOUT

TRIM
PLATE

1-1/4" (32 mm)
MIN. DIA. HOLE
REQUIRED

GASKET

RETAINER

NUT

1-1/2" (38 mm)
MAX. DECK
THICKNESS

CONTROL MODULE

24" (610 mm)
LONG FLEX HOSE

1/2" NPSM TO
3/8" COMPRESSION
CONNECTION

COPPER TUBE
OR FLEX HOSE
(NOT SUPPLIED)

36" (914 mm)
LONG SENSOR
CABLE

TEMPERED
SUPPLY

**HOT AND COLD WATER
SUPPLY APPLICATIONS**
(SPECIFY IN MODEL VARIATION)

BDM VARIATION
(BELOW DECK
MECHANICAL)
MIXING VALVE

3/8" (10 mm)
BAK-CHEK TEE

HOT
SUPPLY

COLD
SUPPLY

**Sloan 10500 Seymour Ave, Franklin Park, IL 60131**
Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

Code 3362157IN • Downloaded 05/11/24 • Revised 01/12/24 • View Latest Version