

OPTIONS**Flush Volume**

- 3.5 gpf (13.2 Lpf) (3.5)
- 1.6 gpf (6.0 Lpf) (1.6)
- 1.28 gpf (4.8 Lpf) (1.28)

Finish

Rough Brass

Activation

Manual Specialty

Valve

Diaphragm

Water Efficiency

- Water Saver
- Low Consumption
- High Efficiency

Bypass

Dual-Filtered Bypass

Fixture Type

Water Closet

Fixture Connection

Rear Spud

Installation

Concealed

L Dimension

- 12 ¾" (324mm) (12-3/4-LDIM)
- 11 ¾" (298mm) (11-3/4-LDIM)
- 8 ¾" (222mm) (8-3/4-LDIM)
- 9 ¾" (248mm) (9-3/4-LDIM)
- 10 ¾" (273mm) (10-3/4-LDIM)
- 2 ¾" (70mm) (2-3/4-LDIM)
- 3 ¾" (95mm) (3-3/4-LDIM)
- 4 ¾" (121mm) (4-3/4-LDIM)
- 5 ¾" (146mm) (5-3/4-LDIM)
- 7 ¾" (197mm) (7-3/4-LDIM)

Wall Box

Standard (not included, order separately)

Handle

- Metal Oscillating (J)
- Front of Valve (H)

Push Button

Image for a standard ROYAL 603 shown

DESCRIPTION

Royal® Concealed Manual Specialty Water Closet PWT Flushometer

FEATURES

- Royal®, Regal® and Sloan® Prison Flushometers feature all the performance benefits of standard concealed, diaphragm model Flushometers with added durability to withstand rough environments
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Concealed Flushometer Installation Instructions for Stainless Steel Fixtures](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Royal Manual Diaphragm Flushometer Repair and Maintenance Guide](#)
- [Concealed Flushometers Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

Less (L/C9A)
3" Metal Oscillating (L3)

Control Stop

1" Straight (E)
Less (L/STOP)
1"
Adjustable Ground Joint for Tek (XDT)
Wheel Handle (K)

Inlet

1"
Back of Valve (B)

Vacuum Breaker

Less (XYV)

Outlet Tube

Trap Primer (TP)

Specialty

PWT

Compliances & Certifications

BAA Compliant
Made in the USA
BABAA Compliant
UPC Certified
cUPC Certified
WaterSense Listed
BREEAM Water Credit
Green Globes Water Credit
LEED V4 Water Efficiency Credit
Satisfies LEED Credits

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.