

**OPTIONS****Flow Rate**

- 0.5 gpm (1.9 Lpm) (0.5GPM)
- 0.35 gpm (1.3 Lpm) (0.35GPM)

**Mixer**

- Back-Check Tee (TEE)
- Below Deck Manual Mixing Valve (BDM)

**NOTES**

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.



Image for a standard SF-2300 shown

**DESCRIPTION**

Sloan® Hardwired-Powered Deck-Mounted Mid Integrated Base Body Faucet

**FEATURES**

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Brass 4 Centerset Hand Washing Faucet with the following features:

- Splash-proof Circuit Control Module
- Adjustable Infrared Sensor Range
- 36" (914 mm) Long Sensor Cable
- 24" (610 mm) Long Flex Hose
- Filtered Solenoid Valve with serviceable Strainer Filter
- Includes Four (4) AA-size Batteries
- Includes appropriate Mounting Hardware
- 1 Year limited warranty

**DOWNLOADS**

- [SF Series Installation Instructions](#)
- [SF Series \(FR\) Installation Instructions](#)
- [SF Series \(SP\) Installation Instructions](#)
- [SFP 35-A Installation Instructions](#)
- [Trim Plate Guide](#)
- [Faucet Spray Heads Repair and Maintenance Guide](#)
- [SF-2300/2350 Repair and Maintenance Guide](#)
- [Additional Downloads](#)

**VIDEOS**

SF-2100/2150/SF-2200/2250/SF-2300/2350/SF-2400/2450  
Parts Breakdown

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • [sloan.com](http://sloan.com)

-  SF-2100/2150/SF-2200/2250/SF-2300/2350/SF-2400/2450  
Module Replacement
-  SF-2100/2150/SF-2200/2250/SF-2300/2350/SF-2400/2450  
Battery Replacement- Sensor Range Adjustment