SLOAN.

OPTIONS

Flush Volume

1.0 gpf (3.8 Lpf) (1.0) 1.5 gpf (5.7 Lpf) (1.5) 0.5 gpf (1.9 Lpf) (0.5) 0.125 gpf (0.5 Lpf) (0.125)

Finish

Rough Brass Brushed Stainless (SF)

Activation

Manual

Valve

Diaphragm

Water Efficiency

Low Consumption Water Saver High Efficiency

Fixture Type

Urinal

Fixture Connection

Rear Spud

Installation

Concealed

L Dimension

10 ¾" (273mm) (10-3/4-LDIM) 3 ¾" (95mm) (3-3/4-LDIM) 6 ¾" (171mm) (6-3/4-LDIM) 7 ¾" (197mm) (7-3/4-LDIM) 8 ¾" (222mm) (8-3/4-LDIM) 4 ¾" (121mm) (4-3/4-LDIM) 2 ¾" (70mm) (2-3/4-LDIM) 5 ¾" (146mm) (5-3/4-LDIM) 12 ¾" (324mm) (12-3/4-LDIM) 9 ¾" (248mm) (9-3/4-LDIM)

Wall Box

Standard (not included, order separately)

Push Button

3" Metal Oscillating (L3) Metal Index (L)

Control Stop

1" Straight (E)



Image for a standard ROYAL 195 shown

DESCRIPTION

Royal® Concealed Manual Urinal Flushometer

FEATURES

- Flush volumes start as low as a pint of water
- Water conservation is aided by the ADA-compliant, non-holdopen handle, which, prevents urinal from exceeding intended flush volume
- Flush accuracy is controlled by CID[™] technology, also enhancing water efficiency
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- Sloan Concealed Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Additional Downloads

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



Ground Joint (GJ) Less (L/STOP)

Compliances & Certifications

BAA Compliant BABAA Compliant Made in the USA cUPC Certified UPC Certified ADA Compliant WaterSense Listed BREEAM Water Credit Green Globes Water Credit LEED V4 Water Efficiency Credit

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com