

**OPTIONS****Flush Volume**

- 1.0 gpf (3.8 Lpf) (1.0)
- 1.5 gpf (5.7 Lpf) (1.5)
- 0.5 gpf (1.9 Lpf) (0.5)
- 0.125 gpf (0.5 Lpf) (0.125)

**Finish**

- Rough Brass
- Brushed Stainless (SF)

**Activation**

- Manual

**Valve**

- Diaphragm

**Water Efficiency**

- Low Consumption
- Water Saver
- High Efficiency

**Fixture Type**

- Urinal

**Fixture Connection**

- Rear Spud

**Installation**

- Concealed

**L Dimension**

- 10 ¾" (273mm) (10-3/4-LDIM)
- 3 ¾" (95mm) (3-3/4-LDIM)
- 6 ¾" (171mm) (6-3/4-LDIM)
- 7 ¾" (197mm) (7-3/4-LDIM)
- 8 ¾" (222mm) (8-3/4-LDIM)
- 4 ¾" (121mm) (4-3/4-LDIM)
- 2 ¾" (70mm) (2-3/4-LDIM)
- 5 ¾" (146mm) (5-3/4-LDIM)
- 12 ¾" (324mm) (12-3/4-LDIM)
- 9 ¾" (248mm) (9-3/4-LDIM)

**Wall Box**

- Standard (not included, order separately)

**Push Button**

- 3" Metal Oscillating (L3)
- Metal Index (L)

**Control Stop**

- 1" Straight (E)

**DESCRIPTION**

Royal® Concealed Manual Urinal Flushometer

**FEATURES**

- Flush volumes start as low as a pint of water
- Water conservation is aided by the ADA-compliant, non-hold-open handle, which, prevents urinal from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

**DOWNLOADS**

- [Sloan Concealed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • [sloan.com](http://sloan.com)

Ground Joint (GJ)  
Less (L/STOP)

**Compliances & Certifications**

BAA Compliant  
BABAA Compliant  
Made in the USA  
cUPC Certified  
UPC Certified  
ADA Compliant  
WaterSense Listed  
BREEAM Water Credit  
Green Globes Water Credit  
LEED V4 Water Efficiency Credit

**NOTES**

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.