SLOAN.

OPTIONS

Power Type

Hardwired

Body Type

Mid

Mounting

Deck

Power Supply

Plug Adapter (PLG) Box Transformer (BOX) Hardwired Less Transformer (HLT)

Sensor Type

Infrared

Flow Rate

0.5 gpm (1.9 Lpm) (0.5GPM) 2.2 gpm (8.3 Lpm) (2.2GPM) 0.35 gpm (1.3 Lpm) (0.35GPM) 1.5 gpm (5.7 Lpm) (1.5GPM)

Spray Type

Multi-Laminar (MLM) Laminar (LAM)

Trim Plate

4" (102mm) (4) 8" (203mm) (8)

Finish

Polished Chrome (CP)

Control Access

Below Deck

Mixer

Back-Check Tee (TEE) Below Deck Thermostatic Mixing Valve (BDT) Above Deck Mixer (ADM) Below Deck Manual Mixing Valve (BDM)

Wash Station

Yes (WS)

Special Features

Battery Backup Less Logo (LL)

Compliances & Certifications

ADA Compliant



Image for a standard ETF-80 shown

DESCRIPTION

Optima® Hardwired-Powered Deck-Mounted Mid Body Faucet

FEATURES

- Commercial Grade Faucet
- ADA Compliant
- Cast Brass Spout
- Quick Connect Fittings
- Integrated Water Shut-off
- Wireless Settings Adjustment
- On-demand or Metered activation
- Hygienic Line Flush
- Water Usage and Battery Strength Reporting
- Self-adapting Sensor

SMART FAUCET ADDITIONAL OPTIONS

- 24VAC plug adapter, power harness assembly or box mount power supply
- Multi-unit gang adapter kit
- 110V or 230V/6VDC plug adapter
- Special PVD finishes available Brushed Stainless, Brushed Nickel, Polished Brass and Matte Black

DOWNLOADS

- Optima Smart Faucet Below Deck Installation Instructions
- Trim Plate Guide
- Faucet Spray Heads Repair and Maintenance Guide
- ETF-80/880 and EBF-85/187 Below Deck Repair and Maintenance Guide
- Additional Downloads



ASME A112.18.1 Compliant EPD HPD IAPMO NSF-61 Proposition 65 TAS UL Certified UPC Certified

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.

VIDEOS

Sloan Connect App®

Sloan Optima Below Deck Faucet