

OPTIONS

Flush Volume

- 3.5 gpf (13.2 Lpf) (3.5)
- 1.6 gpf (6.0 Lpf) (1.6)
- 1.28 gpf (4.8 Lpf) (1.28)
- 2.4 gpf (9.1 Lpf) (2.4)

Finish

- Rough Brass
- Brushed Stainless (SF)

Water Efficiency

- Water Saver
- Low Consumption
- High Efficiency

L Dimension

- 10 ¾" (273mm) (10-3/4-LDIM)
- 8 ¾" (222mm) (8-3/4-LDIM)
- 3 ¾" (95mm) (3-3/4-LDIM)
- 6 ¾" (171mm) (6-3/4-LDIM)
- 4 ¾" (121mm) (4-3/4-LDIM)
- 7 ¾" (197mm) (7-3/4-LDIM)
- 2 ¾" (70mm) (2-3/4-LDIM)
- 5 ¾" (146mm) (5-3/4-LDIM)
- 9 ¾" (248mm) (9-3/4-LDIM)
- 11 ¾" (298mm) (11-3/4-LDIM)

Wall Box

- Standard (not included, order separately)

Handle

- Metal Oscillating (J)
- Front of Valve (H)

Push Button

- 3" Metal Oscillating (L3)
- Less (L/C9A)
- Metal Index (L)

Control Stop

- 1" Straight (E)
- Less (L/STOP)
- Ground Joint (GJ)

Inlet

- Back of Valve (B)

Vacuum Breaker

- Less (XYV)



DESCRIPTION

Royal® Concealed Manual Water Closet Flushometer

FEATURES

- Flush volumes start as low as 1.28 gpf/4.8 Lpf
- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandal-resistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- Wall Box ready
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Sloan Concealed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Concealed Flushometers Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Outlet Tube

Trap Primer (TP)
F100

Bumper

Double Wall (YI)

Special Features

Whitworth Thread (WWT)
2 Wall Bumpers (Y1)

Compliances & Certifications

BAA Compliant
BABAA Compliant
Made in the USA
UPC Certified
cUPC Certified
BREEAM Water Credit
Green Globes Water Credit
LEED V4 Water Efficiency Credit
Satisfies LEED Credits
WaterSense Listed

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.