

OPTIONS

Flush Volume

- 3.5 gpf (13.2 Lpf) (3.5)
- 1.0 gpf (3.8 Lpf) (1.0)
- 1.5 gpf (5.7 Lpf) (1.5)

Finish

- Polished Chrome (CP)
- Brushed Stainless (SF)
- Polished Brass (PB)
- Brushed Nickel (BN)

Water Efficiency

- Water Saver
- Low Consumption

Handle

- Front of Valve (H)
- Saniguard®
- Nickel-Silver (YA)

Push Button

- 3" Metal Oscillating (L3)
- Front of Valve (HL3)

Control Stop

- 1" Straight (E)
- 3/4"
- Ground Joint (GJ)
- Less (L/STOP)
- Wheel Handle (K)

Inlet

- Left of Valve (C)

Vacuum Breaker

- Less (XYV)

Pipe Support

- Solid Ring (YK)

Compliances & Certifications

- BAA Compliant
- BABAA Compliant
- Made in the USA
- ADA Compliant
- UPC Certified
- cUPC Certified
- UL Certified




Image for a standard ROYAL 180 shown

DESCRIPTION

Royal® Exposed Manual Urinal Flushometer

FEATURES

- Includes the required wall plate and a purple wall flange to let users know reclaimed water is in use
- All organic rubber has been replaced with synthetic compounds
- Optional purple handle provides additional indication of reclaimed water use
- Critical components, including cover, valve body, control stop and sweat solder kit, are made of semi-red brass
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Royal Exposed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Royal Manual Diaphragm Flushometer Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.