

CODE NUMBER

2102309

DESCRIPTION

Vitreous China Floor-Mounted Junior Water Closet.

DETAILS

- Flush Volume: 1.1-1.6 gpf (4.2-6.0 Lpf)
- Flush volume determined by the flushometer used with the fixture
- Rim Height: 10 3/4" (273mm)
- Nominal Dimensions: $27" \times 13" \times 10^{3}4" (686 \times 330 \times 273 mm)$

FEATURES

- White Vitreous China
- Floor mounted, floor outlet
- 10¾" rim height for toddlers
- Water spot area: 9½" x 9¼" (24 cm x 23 cm)
- 1½" I.P.S. top spud inlet
- 21/8" fully glazed trapway
- Closet bolts and caps included
- Toilet seat not included
- Static load rating of 1000 lbs. (See Notes)

RECOMMENDED SEATS

- Bemis BB955CT
- Church 1580CT

PLUMBING SYSTEM REQUIREMENTS

• Minimum Flowing Pressure: 25 PSI (172 kPa)

• Maximum Static Pressure: 80 PSI (552 kPa)

DOWNLOADS

- ST 2309 Top Spud Junior Installation Instructions
- SS/ST/SU/WETS/WEUS Fixtures Repair and Maintenance Guide
- Additional Downloads



COMPLIANCES & CERTIFICATIONS



















(ADA Compliant, CalGreen Compliant, CEC Compliant, cUPC Certified, cUPC Green Certified, EPD, HPD, Satisfies LEED Credits, WaterSense Listed, WELL Building Standard)

NOTES

All information contained within this document subject to change without notice.

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1standard. It is important to consider this when planning rough-in and plumbing layouts.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.

Find a compatible flushometer for this water closet.

WaterSense compliant when used with a WaterSense compliant flushometer

WARRANTY

View Warranty Information



ROUGH-IN

