

CODE NUMBER

3315025BT

DESCRIPTION

Bluetooth, Trim Plate: None, Battery Power Supply, Back-Check Tee, Polished Chrome Finish, 0.5 gpm, Multi-Laminar Spray, Infrared Sensor, Optima® Battery or Turbine-Powered Deck-Mounted Low Integrated Base Body Faucet.

DETAILS

• Flow Rate: 0.5 gpm (1.9 Lpm) (0.5GPM) • Spray Type: Multi-Laminar (MLM)

 Sensor Type: Infrared Mounting Type: 4" Centerset

• Mounting Size: 4" Centerset, (3-hole) 1-1/4" to 1-1/2"

• Trim Plate: None

• Power Supply: Battery (BAT)

• Temperature Mixer: Back-Check Tee (TEE)

• Finish: Polished Chrome (CP)

• Factory Default Timeout: 30 seconds • Factory Default Gallons per Cycle: 0.25

FEATURES

ADA Compliant, Water Usage and Battery Strength Reporting, Wireless Settings Adjustment, Commercial Grade Faucet, Integrated Water Shut-off, Hygienic Line Flush, On-demand or Metered Activation, Self-adapting Sensor, Cast Brass Spout, Quick Connect **Fittings**

ELECTRICAL SPECIFICATIONS

• Battery Life: 3 years 8,000 cycles/month Optional power harvesting significantly extends service life

• Sensor Range: 4"-5" (102-127mm) • Timeout Adjustment Settings: 30s

POWER SUPPLY OPTIONS

6VDC Plug Adapter (sold separately), 0362006*

• 6VDC Ganged Adapter Kit (up to 6 units)(sold separately), 0362035*

• 24VAC Box Transformer (up to 3 units)(sold separately), 0345370PK*

• Optional Turbine Energy Harvesting

* when converting units to hardwired with battery back-up

VIDEOS

Sloan Connect App®

Sloan Optima Below Deck Faucet

PVD Special Finishes


DOWNLOADS

• Optima Smart Faucet Below Deck Installation Instructions

• Faucet Spray Heads Repair and Maintenance Guide

• ETF-600/EBF-650 Below Deck Repair and Maintenance Guide







(ADA Compliant, ASME A112.18.1 Compliant, BREEAM Materials Credit, BREEAM Water Credit, CalGreen Compliant, CEC Compliant, cUPC Certified, cUPC Low Lead Compliant, EPD, Green Globes Materials & Resources Credit, Green Globes Water Credit, HPD, IAPMO, LEED Materials & Resources EPD Credit, LEED Materials & Resources HPD Credit, NSF-61, NYC604.4, Proposition 65, Satisfies LEED Credits, TAS, UPC Certified, UPC Low Lead Compliant, WaterSense Listed, WELL **Building Standard)**

RECOMMENDED SPECIFICATION

Faucet shall include cast brass body, quick-connect fittings, twist-off/shut-off solenoid assembly, removable battery cartridge, flexible power supply and allow adjustment of settings wirelessly via Apple or Android smartphones.

NOTES

All information contained within this document subject to change without notice.



OPTIMA® SENSOR FAUCET EBF-650-BAT-TEE-CP-0.5GPM-MLM-FCT

- Trim Plate Guide
- Additional Downloads

Looking for other variations of the EBF-650 product? View the general spec sheet with all options.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.

WARRANTY

View Warranty Information



ROUGH-IN

