

CODE NUMBER

3362158IN

DESCRIPTION

4" Trim Plate, Plug Adapter Power Supply, Back-Check Tee, Polished Chrome Finish, 0.5 gpm, Multi-Laminar Spray, Infrared Sensor, Sloan® Hardwired-Powered Deck-Mounted Mid Body Faucet.

DETAILS

• Flow Rate: 0.5 gpm (1.9 Lpm) (0.5GPM) • Spray Type: Multi-Laminar (MLM)

• Sensor Type: Infrared Mounting Type: Single Hole • Trim Plate: 4" (102mm) (4) • Power Supply: Plug Adapter (PLG)

• Temperature Mixer: Back-Check Tee (TEE)

• Finish: Polished Chrome (CP)

• Factory Default Timeout: 30 seconds • Factory Default Gallons per Cycle: 0.25

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Brass Pedestal Hand Washing Faucet with the following features:

• Adjustable Infrared Sensor Range

• 36" (914 mm) Long Sensor Cable

• 24" (610 mm) Long Flex Hose

• Filtered Solenoid Valve with serviceable Strainer Filter

• Includes Four (4) AA-size Batteries

• Includes appropriate Mounting Hardware

ELECTRICAL SPECIFICATIONS

• Battery Life: 2 years 8,000 cycles/month

• Sensor Range: 4"-7" (102-178mm)

• Timeout Adjustment Settings: 30s

VIDEOS

SF-2100/2150/SF-2200/2250/SF-2300/2350/SF-2400/2450 Parts Breakdown


SF-2100/2150/SF-2200/2250/SF-2300/2350/SF-2400/2450 Module Replacement

SF-2100/2150/SF-2200/2250/SF-2300/2350/SF-2400/2450 Battery Replacement- Sensor Range Adjustment

DOWNLOADS

- SF Series Installation Instructions
- SF Series (FR) Installation Instructions
- SF Series (SP) Installation Instructions
- SFP 35-A Installation Instructions
- Trim Plate Guide
- SF-2400/2450 Repair and Maintenance Guide
- Additional Downloads





COMPLIANCES & CERTIFICATIONS






















cUPC Low Lead Compliant, IAPMO, NSF-61, Proposition 65, UPC Certified, UPC Low Lead Compliant, WaterSense Listed, WELL **Building Standard)**

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the SF-2400 product? View the general spec sheet with all options.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com






WARRANTY

View Warranty Information



ROUGH-IN



HOT AND COLD WATER SUPPLY APPLICATIONS

(SPECIFY IN MODEL VARIATION)

